Stagg pro lighting

www.staggmusic.com

User Manual

HEADBANGER10

SLI MHW HB10

Maintenance

1. Avoid contact with high humidity or direct contact with moisture.
2. Using the product for extended run cycles without pause can shorten lifespan
3. Cleaning the lens and fan assemblies and blowing out dust from the product is mandatory maintenance and will extend lifespan.
4. Never use petroleum-based cleaning agents or solvenst on the product, this will damage the product permanently

Statement

All products are checked carefully before packing and shipping. Should you find the product to be damaged when opening the box, contact your dealer. Any misuse of the product due to neglect of the guidelines in this manual will void your warranty. The dealer or manufacturer can never be held responsible should this occur.
Technical details can be changed without notice

Attention

1. Never use the product in high humidity, in direct or indirect contact with moisture or in locations with high temperatures. Failure to do so will void your warranty.
2. Always place the product on a solid and even surface. When installed with the hanging bracket, always make sure to use an approved mounting clamp and check the mounting points for wear or damage.
3. A trained professional should perform all repairs and maintenance. Never open the product without approval from your dealer.
4. Always use a stable power source within operating specifications.
5. Allow the light to cool down for 20 minutes before re-using.

Product Introduction

- Power Supply AC90-230V, 50Hz-60Hz
- Power consumption: 80W
- 7pcs*10W RGBW LED
- DMX-Control-channels: 7 or 12, user selectable
- Color: RGBW Color-mixing
- Strobe: Flash rate: 0-10Hz
- Dimmer: 0-100%
- Maximum PAN-movement: 540°
- Maximum TILT-movement: 270°
- Master/Slave function

DMX Channel Summary – 7 Channels Mode

CHANNEL	VALUE	FUNCTION
1	0	Stop
	1~255	Adjust Pan
2	0	Stop
	1~255	Adjust Tilt
3	0~10	Close
	11~255	Dimmer
4	0	Close
	1~255	Red
5	0	Close
	1~255	Green
6	0	Close
	1~255	Blue
7	0	Close
	1~255	White

DMX Channel Summary – 12 Channels Mode

CHANNEL	VALUE	FUNCTION
1	0	Stop
	1~255	Adjust Pan
2	0	Stop
	1~255	Adjust Pan fine
3	0	Stop
	1~255	Adjust Tilt
4	0	Stop
	1~255	Adjust Tilt fine
5	0~10	Close
	11~255	Dimmer
6	0	Close
	1~255	Red
7	0	Close
	1~255	Green
8	0	Close
	1~255	Blue
9	0	Close
	1~255	White
10	0~9	Close
	10~255	Color Macros
11	0~9	No strobe
	10~255	Adjust strobe from slow to fast
12	0~127	Stop sound active mode
	128~255	Activate sound active mode

Display Control Instruction

ADDR	DMX Adress	A001-A512
CHND	Channel Mode	7CH/12CH
SLND	Master/Slave	NAST/SL1/SL2
SOUN	Sound Sensitivity	0-100
AUTO	Auto Mode	NO/YES
STBY	Standby	NO/YES
PAN	PAN Reverse	NO/YES
TILT	TILT Reverse	NO/YES
LED	LED On/Off	ON/OFF
DISP	Display On/Off	ON/OFF
TEST	Self Test	
HOUR	Show Total Runtime	
RSET		

IMPORTANT SAFETY INSTRUCTIONS

READ AND KEEP THESE INSTRUCTIONS. HEED ALL WARNINGS.

• If, after you have followed the instructions outlined above, this device fails to function, please contact your dealer. Under no circumstances should this device be opened. Leave all servicing to qualified personnel.

•Electrical appliances must never be used in conditions of high humidity or heat. To prevent any risk of fire or electric shock, never spill or splash liquids on this device. Should this happen, unplug the power cable from the mains outlet and switch off the mixer immediately.

MARKING & CONFORMITY

1. The CE mark on this product means it conforms to the EMC Directive (2004/108/CE), CE marking Directive (93/68/EEC) and Low Voltage Directive (2006/95/EC).

2. The «Crossed-out Wheeled Bin» is to draw your attention to the WEEE (Waste Electric & Electronic Equipment) Directive (2002/96/EC). It means this apparatus must be collected separately for recycling.

3. «RoHS compliant» means this device conforms to the Directive (2002/95EC) on the restriction of the use of certain hazardous substances in electrical and electronic equipments, such as: Mercury, Lead, Cadmium, Hexavalent Chromium, Polybrominated Buphenyl (PBB) and Polybrominated Diphenyl Ethers (PBDE).

DISTRIBUTOR / DEALER